

# **ABO – CENTER**

V/ Henriksens Elektronik

## Tekniske data LS5000

### **TYPE:**

42XX, 1992 - 1993

<b>Specifications</b>	
CTV system	PAL B/G (Single standard)
Picture tube system	Flat square, Hi-Bri, In-Line 110 degrees
Picture tube (visual picture)	66 cm - 25" (59 cm - 23")
Cabinet	Teak - Rorewood - Grey metallic
Contrast screen	With metallized coating
Design	High format cabinet
Main features:	
Operation	Beolink 1000, one-way
TV tuner range	46-855 MHz: VHF,S,Hyper,UHF
Number of TV programmes	32
Satellite	Prepared for Beosat LM kit
No. of satellite programmes	99
Signal/noise level	> 35 dB/1 Vpp and antenna signal > 1mV
Crosstalk between sources	> 45 dB/5 MHz
Teletext	5 alphabet
Teletext memory	4x32 page nos.
Sound system	Nicam EU+A2 stereo decoder+A2 dual language
Speaker system/units	2x Bass Reflex/Full range
Long-term max. output power	2x40 watts / 8 Ohms
Harmonic distortion	< 0.5% at 15 watts
Intermodulation	< 1%
Signal-to-noise ratio	> 50 dB weighted 50 mV(NICAM >70 dB)
Frequency range, audio	25 - 20,000Hz +/- 1.5 dB
Power bandwidth	25 - 20,000Hz
Channel separation	A2 stereo>26(NICAM >70dB)
Bass control	+ / - 8 dB / 100 Hz
Treble control	+ / - 8 dB / 10,000 Hz
Power supply	220 - 240 volts
Power consumption	100 (75 - 165) watts
Power consumption stand-by	3 watts
Dimensions W x H x D	78*47*42 cm
Weight	37 kg
Connections:	
AV 21-pin	
External speakers	
Motorized stand	

# **ABO – CENTER**

V/ Henriksens Elektronik

Stereo headphones	
-------------------	--

S-VHS	
-------	--

ABO . CENTER v/Henriksens Elektronik